

PARALATT 1225

Producer: Aquaba Energie Centrum a.s.

Příčná 1045/2

CZ - 419 01 Duchcov

Product: Mark Paralatt 1225

The wooden anti-slip the grating:

- Thickness: 37 mm
- Standard width in mm: 500, 600, 700, 800, 900, 1000, 1100, 1200, 1300, 1400, 1500, 1600
- Length: according to customer's wishes
- Weight: 20 kg/m²
- The top batten: deciduous profile hardwood without a surface coating
- Bottom belt: softened PVC
- Link: galvanized, stainless steel screws. According to the needs of the customer
- The distance between the upper Rails: 12 mm

Material: The top batten – deciduous wood bars with bottom link--softened and transparent PVC. Both materials are joined by screws.

Characteristics: Own material structure are fixed, stable, flexible and rollable. Gratings resist acids, oils, chemicals and petrol. Gratings are non-conductive with using the non-galvanized screws. The draining of liquids is in all directions.

Usage: Wherever there are required purity of environment (water absorption of wood top rail), a flexible substrate, a heat or electrical influences on heavy industry, to machines such as insulating and anti-fatigue pad. For example - the production hall, the automotive industry, heavy industry, food industry, etc.

Used materials and technological procedures conform to the technical standards according to Czech and European legislation.

According to the law 22/1997 Coll., as subsequently amended, on technical requirements for products in the Czech Republic, are not subject to the obligations of the Paralatt 1225 products conformity assessment; not intended for fixed installation.