

PARALATT 125

Manufacturer: Aquaba Energie Centrum a.s.

Příčná 1045/2

CZ - 419 01 Duchcov

Product: Paralatt 125

PVC anti-slip mats: classification of ČSN EN 649 class 34 + 43

- Thickness: 13 - 14 mm
- Standard width in mm: 250, 325, 400, 475, 550, 700, 625, 775, 850, 1000, 925, 1075, 1150,

1225, 1300, 1375, 1450, 1525, 1600.

- Length: according to customer's wishes, max. 20 m
- Weight: 7, 5 kg/m²
- The color of the top batten: white, grey, beige, blue, green, yellow, brown

Material: the top batten – hardened PVC, the bottom link-softened colorless PVC. Both materials are heat treated and welded without the use of a third of the material.

Characteristics: its material structure are solid, flexible, hygienic, and scrolling. Resist acids, oils, chemicals, corrosion, mineral and sea water, bacteria and inorganic substances. The Mats are hardly flammable a flame retardant and non-conductive. There is the complete ignorance of metal parts and from all sides sealed surfaces for the highest degree of hygiene.

Usage: everywhere, where are placed high demands on hygienic cleanliness, to the wet environment, in the laboratory, for machines such as insulating and anti-fatigue pad.

For Example: chemical laboratories, health, swimming pools, (the option of laying under water)l, production halls, terraces, balconies, bathrooms, saunas, veterinary equipment, automotive, heavy industry, food industry, etc.

According to the law 22/1997 Coll., as subsequently amended, on technical requirements for products in the Czech Republic, products Paralatt 125 are not subject to conformity assessment; not intended for fixed installation .