

PARALATT 518

Výrobce: Aquaba Energie Centrum a.s.

Příčná 1045/2

CZ - 419 01 Duchcov

Product: Paralatt 518

PVC grating for overflowing channel : the grating in fixed overflowing channel

- Thickness: 22 mm – 25 mm
- Width : standard 100 mm - 300 mm, according to the wishes of the customer, till 266mm without lower support (for normal walking)
- Length: according to customer's wishes. 10-15 m
- Weight: 2, 5 kg/bm
- Colour: Standard white, grey, beige according to customer's wishes

Material: the top batten – hardened PVC, the bottom link-softened PVC, colourless. Both materials are heat treated and welded without the use of a third of the material.

Characteristics: for its material structure are fixed, elastic, shockproof , hygienic and scrollable. Resist acids, oils, rust, chlorine, marine and mineral water, chemicals, bacteria and inorganic substances. They are hardly flammable a flame retardant and non-conductive. Resistant to UV radiation. The complete ignorance of metal parts and from all sides sealed surfaces for the highest degree of hygiene.

Usage: everywhere, where are placed high demands on hygienic cleanliness, to the wet environment, in the pool's gutter, for machines in drainage gutters. For Example. the chemical industry, swimming pools, production halls, terraces, balconies, saunas, veterinary equipment, automotive, heavy industry, food industry, etc.

According to the law 22/1997 Coll., as subsequently amended, on technical requirements for products in the Czech Republic, products Paralatt 518 are not subject to conformity assessment; not intended for fixed installation .